

Fetal Monitor

BT-350

- 7" wide TFT color LCD display
- Up to 150 patients data saving
- USB data saving
- Multiple language support
- Built-in quick guide [LCD Type only]
- Waterproof probe
- GE / Philips paper compatible
- Interpretation function



LED Type



LCD Type

Fetal Monitor BT-350

Specifications

FHR	<ul style="list-style-type: none"> Dual pulsed doppler Intensity : 10mW / cm² or less Accuracy : ±2% of range 	<ul style="list-style-type: none"> Ultrasound frequency : 1 MHz FHR range : 30~240 bpm FHR 50~210 bpm FHR 	
FM	<ul style="list-style-type: none"> Auto-detection of dual fetal movement 		
UC	<ul style="list-style-type: none"> External type Reference(zero) control 	<ul style="list-style-type: none"> Frequency response : DC~0.5HZ Measurement range : 0~99units 	
Printer	<ul style="list-style-type: none"> Thermal array type Auto print : off, 10, 20, 30, 40, 50, 60 min 	<ul style="list-style-type: none"> Print speed : 1, 2, 3cm/min, high speed(Trend mode) Paper feeding function 	
Display	<ul style="list-style-type: none"> 3 Channels(FHR I , FHR II , UC) 7" Wide TFT-color LCD : LCD type Large 7-segment LED type 		
Function	<ul style="list-style-type: none"> Mark function Auto print function Interpretation function 	<ul style="list-style-type: none"> FHR II offset function Fetal movement print function Multi-language & quick guide function : LCD type 	
Trend	<ul style="list-style-type: none"> USB Data Saving 	<ul style="list-style-type: none"> Data saving for 450 hours(3hr/person) : LCD type only 	
Power	<ul style="list-style-type: none"> Input : AC 100~240V(50/60Hz) Battery operation(Optional) 	<ul style="list-style-type: none"> Output : DC 18V, 2.5A Consumption : 80VA 	
Dimension	<ul style="list-style-type: none"> 80 mm(H) x 330 mm(L) x 280mm(D) 		
External link	<ul style="list-style-type: none"> Wire : RS-232C 	<ul style="list-style-type: none"> Wireless : Bluetooth 	
Accessory standard	<ul style="list-style-type: none"> Ultrasound doppler probe 2ea Event marker jack 1ea Power adaptor & Cord 1ea Probe belt 3ea 	<ul style="list-style-type: none"> UC probe 1ea Print paper 2ea Ultrasound gel 1ea Operation manual 1ea 	<ul style="list-style-type: none"> Probe holder 2ea
Optional	<ul style="list-style-type: none"> AST(Acoustic stimulator) Bluetooth system 	<ul style="list-style-type: none"> Rechargeable battery Wall mount bracket 	<ul style="list-style-type: none"> Carrying bag
Warranty	<ul style="list-style-type: none"> 2 years(Accessory excluded) 		

PC Interface (Central monitoring system)

BCM-350

- Remote control up to 8 monitors
- Fetal heart sound record & play
- Unlimited multi language support
- Wire(RS-232C)and wireless(Bluetooth) connection
- Network system by LAN connection(BCM-350 only)
- Remote real-time picking-up fetal heart sound(Patent)

Installation



Notebook style



Wall mount style

