

ProLED SERIES



Medical Grade Aluminium Alloy | Adjustable Focus | Maximum Brightness



ProLED DOUBLE DOME

Intensity	1,60,000 + 1,60,000 Lux
Shadowless Feature	Yes
Numbers of LEDs	48 + 48 (Warm + Cool White)
Intensity Control	10-100 Digital Capacitive Touch (Fully Remote Controlled)
Fitting Options Available	Ceiling Mounted - 340 Degrees/ 360 Degrees
Spot Diameter	100-150 mm
Depth of Light Penetration	150 mm
Colour Temperature	3800 - 4800K
Colour Rendering Index	93 Ra
Focusing	Adjustable
LED Average life	>50,000 Hrs.
Diameter of Light	700 mm + 700 mm
Power Supply	220V/50Hz AC
Power Consumption	60 + 60 Watt
Optional Special Features	Mobile App Connectivity, External Wall Panel, Battery Backup

Features


Fully Aerodynamic German design for laminar flow, ClearVision Technology for better viewing during long hours of surgery, Shadowless Light, Memory Function, High Quality Sterilizable Handle suitable for autoclave, Unbreakable Fire-Resistant Polycarbonate Body, Fast Disinfection Process, Protects UV and IR rays and Improves light penetration for deep cavity surgeries



Memory Function



E Endo Mode


Battery Backup: Optional

ProLED SINGLE DOME

Intensity	1,60,000
Shadowless Feature	Yes
Numbers of LEDs	48 (Warm + Cool White)
Intensity Control	10-100 Digital Capacitive Touch (Fully Remote Controlled)
Fitting Options Available	Ceiling Mounted - 340 Degrees/ 360 Degrees
Spot Diameter	100-150 mm
Depth of Light Penetration	150 mm
Colour Temperature	3800 - 4800K

Features

Fully Aerodynamic German design for laminar flow, ClearVision Technology for better viewing during long hours of surgery, Shadowless Light, Memory Function, High Quality Sterilizable Handle suitable for autoclave, Unbreakable Fire-Resistant Polycarbonate Body, Fast Disinfection Process, Protects UV and IR rays and Improves light penetration for deep cavity surgeries



Memory Function



E Endo Mode


ProLED MOBILE MOUNTED